



Technical Specifications

Nortel IP Phone 1150E


Enhancing service levels in IP Contact Centers

The Nortel IP Phone 1150E with Gigabit Ethernet brings best-in-class IP Telephony and advanced communication features to ACD environments and the IP Contact Center. An ideal solution for agents and supervisors, the multi-line IP Phone 1150E leverages the award-winning features and design of the IP Phone 1100 Series for a superior user experience, while adding dedicated agent and supervisor fixed keys along with IP delivery of highly-desired Contact Center features.

With a large, high-resolution, pixel-based, graphical grayscale display, a USB port supporting an enhanced navigation experience, Gigabit Ethernet integration for support of collocated PC traffic and standard Bluetooth headset profile support for agent mobility, the IP Phone 1150E delivers a powerful combination of features to maximize productivity, enhance customer service levels, reduce costs and ultimately, drive increased business performance.

Key features and benefits include:

- > Multi-line IP Phone supports up to twelve line/programmable feature keys¹, four context-sensitive soft label keys² and twelve fixed keys common to the IP Phone 1100 Series
- > Seven additional fixed keys with built-in LEDs dedicated to IP Contact Center agents including: In-Calls, Not Ready, Make Set Busy, Supervisor, Supervisor Listen/Talk, Emergency and Activity³



Nortel IP Phone 1150E



¹ IP Phone 1150E supports up to six line/programmable feature keys. On Nortel Communication Servers, which support the “shift” function, up to twelve line/programmable feature keys are supported.
² Context-sensitive soft label keys are Nortel Communication Server dependent.
³ Activity fixed key requires Nortel Communication Server development.

- › Optional Supervisor configuration delivers seven fixed keys including Observe Agent, Call Agent, Answer Agent, Answer Emergency, Display Agents, Interflow and Night Service⁴
- › One additional feature key with built-in LED, programmable for any commonly used telephony or ACD features⁵
- › High-resolution, fully-backlit, pixel-based, eight-level grayscale display, which combined with a multi-position footstand, optimizes viewing under varied lighting conditions
- › Four-way navigation cluster with “Enter” key for maximum choice and flexibility in applications navigation and entry
- › Built-in USB port for support of standard USB mice, USB keyboards, devices offering USB keyboard emulation and USB powered hubs, enhancing user experience when interacting with applications and selecting menu options
- › An integrated Bluetooth® 1.2 Audio Gateway for support of standard Bluetooth headset profiles, boosting agent productivity with greater freedom at the desktop
- › An integrated 10/100/1000 IEEE Base-T Ethernet Switch with LAN and PC ports, supporting switching of both IP Phone traffic and the traffic from a collocated PC
- › Gigabit Ethernet switch integration for investment protection at the desktop, addressing the ongoing growth of multimedia-intensive traffic from a collocated PC, enabling it to be switched through the PC port of the IP Phone 1150E
- › Dual headset jacks for agent support and supervisor plug-in, leveraging third-party headsets
- › 802.3af Power over Ethernet as standard or local power option via a separately orderable AC power adapter
- › Visual Alerting/Message Waiting Indication LED for incoming call and voice message pending notification
- › Feature Status LED to signal users of firmware downloads in progress
- › Secured communications with standards-based signaling and media path encryption along with authentication for network access control
- › Supports 802.1ab Link Layer Discovery Protocol, simplifying network discovery and inventory management
- › Lockable Tools Menu for local access to configuration, diagnostic and user preference options with USB navigation support
- › Supports Unicode for expanded language and complex font presentation on the phone display⁶
- › Tight linkage with Nortel Communication and Application Servers, offering a rich suite of reliable, business-grade telephony, IP Contact Center communication and application features
- › Proactive Voice Quality Management (PVQM) for enhanced administration and diagnostics
- › Added convenience and time savings with field-upgradeable firmware using Trivial File Transfer Protocol (TFTP) or UNISlim File Transfer Protocol (UFTP)⁷

⁴ IP Phone 1150E is shipped with the agent configuration as standard. An optional Supervisor Keycap Kit is available for purchase separately to customize the IP Phone 1150E keys for supervisor use.

⁵ Additional Feature key requires Nortel Communication Server development.

⁶ Nortel Communication Server/minimum release dependent. Consult Nortel server documentation for further details.

⁷ UNISlim File Transfer Protocol support is Nortel Communication Server dependent. Consult your Nortel Communication Server documentation of choice to confirm whether UFTP support is available.

Technical specifications

Platform support

- Nortel Communication Server 1000 Release 4.5 and later
- Nortel Communication Server 2100 (initial support on Release SE10 and later)
- Media Gateway 1000B Expansion Chassis

IP Contact Center Server

- Symposium Express Contact Center (SECC) Release 4.2
- Symposium Contact Center Server (SCCS) Release 5.0
- Contact Center Release 6.0

Display

- High resolution, fully backlit, bitmapped, graphical Film Super Twist Nematic (FSTN) Liquid Crystal Display, 240 x 160 pixel, with support of eight grayscale levels
- Contrast settings, accessible via Local Tools Menu, to enhance agent and supervisor viewing experience
- Configurable backlight timer with 5, 10, 15, 20-minute, 1-hour, 2-hour settings and a “Sleep Never” option for 24x7 Contact Center environments
- Supports Unicode for expanded language and complex font presentation on the phone display⁸

Footstand and adjustments

- Desktop viewing adjustments: 32.5, 40, 47.5 and 55 degree angle height positions
- Wall mount option: minus 5 degrees

Fixed and soft label keys

- Twelve fixed business telephony keys including Hold, Goodbye, Volume Up, Volume Down, Mute, Directory, Message/Inbox, Shift/Outbox, Quit, Copy, Expand and Services

- Four context-sensitive soft label keys for easy-to-use navigation⁹
- Seven *dedicated* Agent fixed keys with built-in LEDs: Listen/Talk, In-Calls, Not-Ready, Make Set Busy, Supervisor, Emergency and Activity¹⁰ (default configuration)
- Seven *dedicated* Supervisor fixed keys with built-in LEDs: Observe Agent, Call Agent (direct line), Answer Agent, Answer Emergency, Display Agents, Interflow and Night Service (optional configuration with purchase of Supervisor Keycap kit)
- One additional programmable fixed key (“Feature Key”), which can be flexibly assigned to support a standard telephony or ACD specific feature¹¹

Navigation cluster

- Four way navigation cluster (left, right, up, down arrows) plus Enter key¹²

USB

- Integrated USB port for standard USB mice, keyboards, keyboard emulation devices and powered hubs

Headset support

- Integrated *Bluetooth* 1.2 Audio Gateway supports standard third-party Bluetooth headset profiles (*Bluetooth* Power Class 2) for intra-office mobility up to 10m/33ft away from audio gateway
- Support for third-party wired and wireless headsets¹³
- Dual headset jacks: Agent and Supervisor

Call Recording

- Supports transmission of duplicate media streams with Nortel Contact Recording and Quality Monitoring (CRQM)

Expansion Module

- Supports 18-button Expansion Module for IP Phone 1100 Series via integrated Expansion Module/ Console port¹⁴

User Selectable Ringtones

Color

- Graphite with Silver Metallic Bezel finish

Dimensions and weight

- Dimensions including footstand (HxWxD):
 - 55 degree configuration: 9.05 in x 6.14 in x 7.36 in/229.9mm x 155.9mm x 187.1 mm
 - 32.5 degree configuration: 7.12 in x 6.14 in x 8.48 in/180.9mm x 155.9 mm x 215.4 mm
 - Minus 5 degree configuration (wall-mount): 9.79 in x 6.14 in x 3.29 in/ 248.6mm x 155.9 mm x 83.6 mm
- Weight: 1.70 lbs/771 g

Connectivity/data rates

- Integrated 10/100/1000 IEEE Base-T auto-sensing Ethernet Switch for shared PC access (one LAN and one PC port)
- Manually configurable for 10 and 100 Mbps speeds when used with Ethernet Switches that do not support auto-sensing
- Minimum Category 5e cabling required for Gigabit Ethernet deployment (Category 5e cable included as standard)

Power

- Supports IEEE 802.3af power standard, pre-standard Nortel and Cisco proprietary powering schemes¹⁵
- Power dissipation: IEEE Power Class 3. Gigabit Ethernet: 7.2 watts idle, 9.6 watts full utilization (exclusive of cable loss); 100 Mbps: 5.0 watts idle; 6.8 watts full utilization
- Universal local AC power adapter as option (“brick style”) supported (100/240 VAC, 50/60Hz power adapter delivering 48V DC @ 0.52A max)
- AC power cable (country specific) — separately orderable
- USB port power: 100mA power; With powered USB hub, supports up to 500mA

Loudspeaker

- Integrated high-quality speaker (Listen only and Audio Paging)

Administration and Security

- Supports 802.1ab Link Layer Discovery Protocol (LLDP) for network discovery and inventory management
- Static, Partial and Full Dynamic Host Control Protocol settings (Full DHCP factory default)

⁸ Nortel Communication Server/minimum release dependent. Consult Nortel server documentation for further support details.

⁹ Context-sensitive soft label key functionality is Nortel Communication Server 1000 Release 5.0 dependent.

¹⁰ Activity Key requires Nortel Communication Server development. Consult your Nortel representative for timing details.

¹¹ Additional Feature Key requires Nortel Communication Server development. Consult your Nortel representative for timing details.

¹² The Enter key can be used for selection of items within the IP Phone 1150E Local Tools Menu.

¹³ Wireless headsets supported with agent configuration only.

¹⁴ Number of Expansion Modules supported is Nortel Communication Server dependent. Consult the Nortel Communication Server documentation of choice for the maximum number of modules that can be cascaded.

¹⁵ Cisco pre-standard support includes Catalyst 3350, 450E and 6503 Ethernet Switches with software versions: 3350 – IOS 12.1 (1.3); 4503-CATOS 7.6 (3); 6503-CATOS 8.3 (2).

- Network authentication via 802.1x and Extensible Authentication Protocol (EAP) for support within MD-5 enabled networks
- Signaling encryption via Advanced Encryption Standard (AES) 128-bit¹⁶
- RFC 3711 compliant Media encryption via Secure Real-Time Protocol (sRTP) Pre-shared Key and Public Key Infrastructure¹⁷
- Supports Nortel Proactive Voice Quality Management (PVQM) for enhanced administration and diagnostics

Protocols

- E.164 dialing

Audio Quality of Service

- G.711 a-law, G.711 µ-law, G.729a and Annex B
- 802.1p/Q, DiffServ and VLAN tagging of telephony port traffic
- Supports echo cancellation and silence suppression

Operating temperature

- +5°C to +40°C/+40°F to +104°F

Relative humidity

- 5% to 95% (non-condensing)

Storage temperature

- -40°C to +70°C/-40° to +158°F

EMC

- United States: FCC 47 CFR Part 15 Class B
- Canada: ICES-003 Class B
- Australia/New Zealand:
 - AS/NZS 3548 Class B
 - CISPR 22 Class B
- European community:
 - EN55022:1998+A1+A2 (Class B)
 - EN 55024:1998+A1+A2
 - EN 61000-3-2
 - EN 61000-3-3
- Korea MIC
- China CCC
- Japan VCCI

Safety

- United States: UL 60950-1 1st Edition
- Canada: CSA 60950-1-03
- European Community: EN 60950-1 +A11
- Australia/New Zealand: AS/NZS 60950.1: 2003
- IEC 60950-1
- Mexico NOM approvals

Bluetooth

- USA: FCC Part 15 Wireless Certification
- Canada: IC RSS 210 Wireless Certification
- EN 300 328
- EN 301 489-1/EN 301 489-17
- Japan METI Wireless approval
- Korean Wireless approval

US/Canada/Australia/

EU countries

- US/Canada: Hearing Aid Compatibility (HAC) as per FCC Part 68 and Industry Canada CS-03 Part V
- Australia: AS/ACIF 004
- New Zealand PTC 220
- Complies with Reduction of Hazardous Substances (RoHS) - (6 of 6) as part of European Union Environmental Directive
- Complies with the essential requirements and other relevant provisions of Directive 1999/5/EC
- American Disabilities Act (ADA) compliant dialpad

¹⁶ Requires deployment of Secure Multimedia Controller 2450 (SMC 2450) on Nortel Communication Server 1000 in support of signaling encryption.

¹⁷ Public Key Infrastructure is Nortel Communication Server/minimum release dependent. Consult Nortel server documentation for support details.

Nortel is a recognized leader in delivering communications capabilities that make the promise of Business Made Simple a reality for our customers. Our next-generation technologies, for both service provider and enterprise networks, support multimedia and business-critical applications. Nortel's technologies are designed to help eliminate today's barriers to efficiency, speed and performance by simplifying networks and connecting people to the information they need, when they need it. Nortel does business in more than 150 countries around the world. For more information, visit Nortel on the Web at www.nortel.com. For the latest Nortel news, visit www.nortel.com/news.

For more information, contact your Nortel representative, or call 1-800-4 NORTEL or 1-800-466-7835 from anywhere in North America.

Nortel, the Nortel logo, Nortel Business Made Simple, the Globemark and Symposium are trademarks of Nortel Networks. All other trademarks are the property of their owners.

Copyright © 2007 Nortel Networks. All rights reserved. Information in this document is subject to change without notice. Nortel assumes no responsibility for any errors that may appear in this document.

NN117780-102207

In the United States:

Nortel
35 Davis Drive
Research Triangle Park, NC 27709 USA

In Canada:

Nortel
195 The West Mall
Toronto, Ontario M9C 5K1 Canada

In Caribbean and Latin America:

Nortel
1500 Concorde Terrace
Sunrise, FL 33323 USA

In Europe:

Nortel
Maidenhead Office Park, Westacott Way
Maidenhead Berkshire SL6 3QH UK
Phone: 00 800 8008 9009

In Asia:

Nortel
United Square
101 Thomson Road
Singapore 307591
Phone: (65) 6287 2877



BUSINESS MADE SIMPLE

