



5360 IP Phone Specifications

AC Adapter		Power Consumption		Processor Type	Speed	DSPs Number	Speed	Silicon	CODEC / Wideband
Output: 48 VDC	LAN Power	10 / 100 Mb Mode	Gb Mode	TNETV1050 (MIPS)	165 MHz	1	125 MHz	130µ CMOS	G.722
Input: 100 V – 240 V 50 Hz – 60 Hz		Idle: 4.2 W Typical: 7.4 W Max: 7.9 W	Idle: 4.8 W Typical: 8.6 W Max: 9.2 W						
RAM	ROM	Voice Traffic	Signaling	Voice QoS	Size (L x W x H)	Weight	MTBF Rate	CODEC / Compression	
64 MB	32 MB	RTP over UDP	MI-NET over TCP	IEEE 802.1p/q	10.1 in x 7.5 in x 7.1 in (25.6 cm x 19.0 cm x 18.0 cm)	2.55 lbs or 1.16 Kg	50 Years	G.711, G.729a	

Global Headquarters	U.S.	EMEA	CALA	Asia Pacific
Tel: +1(613) 592-2122 Fax: +1(613) 592-4784	Tel: +1(480) 961-9000 Fax: +1(480) 961-1370	Tel: +44(0)1291-430000 Fax: +44(0)1291-430400	Tel: +1(613) 592-2122 Fax: +1(613) 592-7825	Tel: +852 2508 9780 Fax: +852 2508 9232

www.mitel.com



For more information on our worldwide office locations, visit our website at www.mitel.com/offices

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2009, Mitel Networks Corporation. All Rights Reserved.

GD 1031_4792 PN 51015312RB-EN



MITEL

5360 IP Phone

Enriches the End-User Experience

The Mitel® 5360 IP Phone is Mitel's latest state-of-the-art IP phone, which includes a large, color, touch-sensitive, graphical display screen for easy access to communications information, timesaving applications, and extensive features. It provides professionals with an intuitive color interface for easier viewing and navigation, of both phone functions and productivity-enhancing applications. The 5360 IP Phone color phone with Web capabilities is poised to deliver a whole series of HTML-based applications. The phone boasts a seven-inch touch-screen display, which grants access to the applications. The device also features wideband audio, embedded Gigabit Ethernet, and a built-in HTML toolkit for application development. And, whether deployed on premises or remotely as a teleworker, the 5360 IP Phone delivers the extensive set of the Mitel Communications Director (MCD) features directly to the desktop.

Delivers Rich, Intuitive, Visually-Pleasing Telephony Functions and Applications

The 5360 IP Phone provides a full-color user interface to deliver a significantly-augmented and visually-pleasing user experience when running productivity-enhancing applications. It combines a rich color display with superior acoustic sound to offer our customers a visually-pleasing user interface,

an incredible-sounding voice experience, and a future-proof platform with embedded Gigabit Ethernet. Additionally, peripherals like the 5310 IP Conference Unit, the Cordless Accessories Module, and the Wireless LAN Stand allow the 5360 IP Phone to be customized to suit a user's specific needs.



DATA SHEET



5360 IP Phone

The 5360 IP Phone is shown with the optional Cordless (DECT) Handset.

Addresses Vertical Market Requirements

The 5360 IP Phone delivers the latest technology and advancements in IP telephony. It not only addresses the needs of executives and major decision makers, but also brings network data and applications to users without PCs. Enterprise executives, managers, and call center supervisors will appreciate the convenience and productivity benefits inherent in a large-screen, color-graphic display design. Hospitality guests will not only benefit from the 5360 IP Phone's extensive telephony capabilities, they will also experience its vibrant, colorful, innovative, and productivity-enhancing HTML applications delivered right to the display.

Features

- Seven-inch backlit, high-resolution (800 pixels x 480 pixels), color, touch-screen display with brightness controls
- Touch-screen access to features and applications
- Colorized display of content and applications to improve visibility and usability
- Dual embedded Gigabit Ethernet ports (LAN and PC)
- 48 programmable, multi-function, self-labeling keys, provided in three pages of 16 keys each (for one-touch access to speed calls, line appearances, features, and applications)
- Six context-sensitive softkeys for intuitive access to features and functionality
- Gadget Sidebar provides one-touch access to embedded applications such as Call History, Visual Voice Mail, People, Call Forwarding, Conference application, Brightness options, HTML applications, and the main Phone application
- Wideband-audio ready – hardware ships with a wideband handset (7 kHz) standard
- Peripherals and modules support: Mitel Cordless Handset / Headset, Mitel Line Interface Module, Mitel 5310 IP Conference Unit, Mitel Wireless LAN Stand
- 10 fixed function hard keys: hold, menu, message, speaker, mute, transfer / conference, redial, cancel, volume / ringing / contrast up and down
- Backlit display with variable brightness control including a backlighting-off mode
- HTML Desktop Toolkit support for applications development
- Multiple-languages support built-in (English, French, Spanish, German, Italian, Dutch, Portuguese, and simplified Chinese)
- Handsfree speakerphone operation (full duplex)
- Designed for power conservation: reduces power consumption for overall energy saving

Dual Port

Two 10 / 100 / 1000 MB switched Ethernet ports – one connects the 5360 IP Phone with an Ethernet wall jack, the other with the user's PC.

Powering Options

The 5360 IP Phone is 802.3af Power over Ethernet compliant and can be powered via a powered switch, a midspan power hub, or by local 48 V Ethernet Power or 48 VDC Gigabit Ethernet Power Adapter.

Environmental Conditions

	Temperature	Humidity
Operational	+4°C to +49°C	34% at +49°C 95% at +29°C
Storage	-40°C to +66°C	15% at +66°C 95% at +29°C

System Software Requirements

- Mitel Communications Director (MCD) Release 4.0 SP1 or later
- Mitel Border Gateway (MBG) Release 5.2 SP1 or later
- HTML Toolkit Release 2.1 or later

Regulatory Standards

EMC

CANADA:
ICES-003 (CLASS B)

USA:
CFR Title 47, Part 15 (CLASS B)

EU:
EN55024 (EU)
EN55022 (Class B)

AUSTRALIA / NEW ZEALAND:
AS / NZS CISPR 22

BRAZIL:
Resolution No. 442 / 2006 (Brazil)

CHINA:
GB9254

Safety

CANADA:
CSA C22.2 No. 60950-1

USA:
UL 60950

EU:
EN 60950
EN 60950-1

AUSTRALIA / NEW ZEALAND:
AS / NZS 60950-1

BRAZIL:
Resolution 238 / 2000 (Brazil)

CHINA:
GB4943

Telecom

CANADA:
CS03 Part V
(Hearing Aid Compatible)

USA:
FCC part 68 (CFR 47)
(Hearing Aid Compatible)

AUSTRALIA / NEW ZEALAND:
PTC220
AS / ACIS, S004